

DEVOTION CORPORATION

30 rokov skúseností vo výrobe kotlov & tepelných čerpadiel



Quotation Sheet - 2024

Trade Terms: FOB Revúca

<b>Thermax A Series</b> <b>R32 DC Full Inverter Monoblock Heat Pump</b> Heating   Cooling   DHW							
			Shiny Silver	Black Pearl	Matte Gray	ABS Gray Plastic	
<b>MODEL NAME</b>			<b>HEAW08MRN3-A</b>	<b>HEAW10MRN3-A</b>	<b>HEAW12MRN3-A</b>	<b>HEAW14MRN3-A</b>	<b>HEAW16MRN3-A</b>
<b>ABS Plastic Panel</b>			3,720.00 €	4,044.00 €	4,320.00 €	4,836.00 €	4,992.00 €
<b>Galvanized Steel Panel</b> <b>Shiny Silver/Black Pearl/Matte Gray</b>			60.00 €	60.00 €	60.00 €	60.00 €	60.00 €
Power Supply	V/Ph/Hz		220V/1ph				
Heating A7 / W35	Capacity	kW	8.00	10.00	12.00	14.00	16.00
	Rated input	kW	1.66	2.08	2.55	3.11	3.56
	COP		4.81	4.81	4.70	4.50	4.50
Heating A7 / W45	Capacity	kW	8.00	10.00	12.30	14.00	16.00
	Rated input	kW	2.13	2.67	3.32	4.00	4.57
	COP		3.75	3.75	3.7	3.5	3.5
Heating A7 / W55	Capacity	kW	7.50	9.50	11.50	14.00	16.00
	Rated input	kW	2.46	3.11	3.77	5.09	5.82
	COP		3.05	3.05	3.05	2.75	2.75
Cooling A35 / W18	Capacity	kW	7.90	9.90	12.00	12.90	14.90
	Rated input	kW	2.18	2.18	3.04	4.38	4.38
	EER		4.55	4.55	3.95	3.4	3.4
Cooling A35 / W7	Capacity	kW	6.20	8.20	9.84	12.00	14.00
	Rated input	kW	2.52	2.52	3.02	5.19	5.19
	EER		2.46	3.25	3.26	2.31	2.70
ERP	Water outlet at 35°C		A+++	A+++	A+++	A+++	A+++
	Water outlet at 55°C		A++	A++	A++	A++	A++
SCOP	Water outlet at 35°C		4.98	4.98	5.33	4.83	4.83
	Water outlet at 55°C		3.35	3.35	3.70	3.36	3.36
Sound power Level3	Heating A7W35	dB	60	60	65	68	68
Refrigerant / Filling			R32/1.2KG	R32/1.2KG	R32/1.5KG	R32/1.8KG	R32/1.8KG
Compressor	Type		R32 DC Twin Rotary				
Outdoor fan	Motor type		DC motor				
	Number of fans		1				
Air side heat exchanger			Φ7 Fin coil				
Water side heat exchanger			Brazeed Plate				
Throttle	Type		Electronic Expansion Valve				
Water pump	Type		DC inverter				
	Max. pump head	m	9				
Expansion vessel	Volume		5				
	Max. working pressure	bar	8				
Safety valve	Pressure		0.36				
Water side connection			R5/4"				
Outdoor air temperature range	Cooling	°C	-5 ~ -43				
	Heating	°C	-25 ~ -35				
	DHW	°C	-25 ~ -43				
Water outlet temperature range	Cooling	°C	5 ~ 30				
	Heating	°C	12 ~ 65				
	DHW ( tank )	°C	10 ~ 60				
Warranty	2 roky plná záruka + 5 rokov predĺžená záruka na kompresor a výmeník - spolu až (7 rokov záruky)						
Certificates	CE / ERP A+++ / KeyMark / RoHS / SGReady / ISO / LVD / EMC						
Unit Dimension (W*D*H)mm	1128*500*915						
Packaging Dimensions (W*D*H)mm	Carton+Wood Base		1225*540*1042				
	Wooden Crate		1265*580*1062				
Net/Gross Weight	KG	108/142	108/142	114/148	120/154	120/154	
Poznámky: 1. Príslušné normy a legislatíva EÚ: EN14511; EN14825; EN50564; EN12102; (EÚ) č. 811/2013; (EÚ) č. 813/2013; Ú. v. EÚ 2014/C 207/02. 2. Sezónne testy energetickej účinnosti v priemerných klimatických podmienkach. 3. Podmienky testu akustického výkonu : EN12102-1 4. Táto cenová ponuka je platná do 30. decembra 2024							
Vaculka Peter (Director SR)		Email: heta@heta.sk		www.heta.sk		Whatsapp/Mobile +421 918 040 255	